

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) An apparatus for connecting a TV (Television Set) and a computer, comprising:

a TV coding unit for encoding control signals including ~~a TV signal~~ at least one of a mouse signal, a keyboard signal, a microphone signal and control signals for controlling a computer, which are generated in a TV and generating a first packet signal by using the encoded control signals;

a computer coding unit for encoding ~~[[a]] computer signal signals~~ including at least one of a video signal, an audio signal and a control signal generated in ~~a the~~ computer and generating a second packet signal by using the encoded computer signals;

a TV transmission and receiving unit, provided in the TV, for receiving the first packet signal from the TV coding unit, transmitting the received first packet signal to the computer and receiving the second packet signal from the computer;

a computer transmission and receiving unit, provided in the computer, for receiving the second packet signal from the computer coding unit, transmitting the received second packet signal to the ~~outside TV~~ and receiving the first packet signal from the TV;

a TV decoding unit, provided in the TV, for receiving the second packet signal from the TV transmission and receiving unit, decoding the ~~same received second packet signal~~ and recovering the decoded second packet signal into an original signal the video signal, the audio signal and the control signal of the computer;

a computer decoding unit for receiving the first packet signal from the computer transmission and receiving unit, decoding the received first packet signal and recovering the decoded first packet signal into an original signal the mouse signal, the keyboard signal, the microphone signal and the control signals for controlling the computer; and

a transmission line connected between the TV transmission and receiving unit of the TV and the computer transmission and receiving unit of the computer for transmitting the first packet signal and the second packet signal.

2. (Original) The apparatus of claim 1, wherein said transmission line includes:

a first transmission line for transmitting the first packet signal from the TV transmission and receiving unit to the computer transmission and receiving unit; and

a second transmission line for transmitting the second packet signal from the computer transmission and receiving unit to the TV transmission and receiving unit.

Claims 3-20. (Canceled)

21. (Currently Amended) A method, comprising:  
encoding a signal output from a television circuit of a television; ~~and~~  
sending the encoded signal to a personal computer,  
wherein the encoded signal output from the television circuit includes data for  
controlling a function performed by the personal computer;  
receiving the signal sent from the television;  
decoding the received signal for input into a circuit of the personal computer; and  
performing the function of the personal computer according to the decoded  
signal.

22. (Canceled)

23. (Currently Amended) The method of claim 21, wherein the data includes one of  
mouse data, ~~and~~ keyboard data and microphone data.

24. (Currently Amended) The method of claim 21, wherein the ~~data includes~~  
~~microphone data~~ signal output from the television is received along a wireless link.

25. (Previously Presented) The method of claim 21, wherein the encoded signal  
output from the television circuit is wirelessly transmitted to the personal computer.

26-30. (Canceled)

31. (Currently Amended) A system, comprising:  
a first interface unit coupled to a television; and  
a second interface unit coupled to a personal computer,  
wherein the first interface unit sends a first signal generated in the television to the personal computer over a communications link and the first signal controls a function performed by the personal computer, and the second interface unit sends a second signal generated in the personal computer to the television over the communications link and the second signal includes at least one of a monitor display signal and a sound signal to be projected and to be played through the television.

32. (Canceled)

33. (Currently Amended) The system of claim 31, wherein the first signal includes at least one of mouse data and keyboard data.

34. (Currently Amended) The system of claim 31, wherein the first signal includes microphone data.

35. (Previously Presented) The system of claim 31, wherein the communications link is a wireless link.

36. (New) A method for controlling a computer at the side of a TV (Television set), comprising:

encoding control signals including at least one of a mouse signal, a keyboard signal, a microphone signal and control signals for controlling a computer, which are generated in a TV and generating a first packet signal by using the encoded control signals;

encoding computer signals including at least one of a PC monitor display signal, sound signals and control signals generated in the computer and generating a second packet signal by using the encoded computer signals;

receiving the first packet signal from the TV, transmitting the received first packet signal to the computer and receiving the second packet signal from the computer;

receiving the second packet signal from the computer, transmitting the received second packet signal to the TV and receiving the first packet signal from the TV;

decoding the received second packet signal and recovering the decoded second packet signal into the PC monitor display signal, the sound signals and the control signals of the computer; and

decoding the received first packet signal and recovering the decoded first packet signal into the control signal including the mouse signal, the keyboard signal, the microphone signal and the control signals for controlling the computer.